









P.C. MOUNTING



Schematic



Model NO.	TYPE		
MSDS-13L	ON	NONE	ON
MSDS-14L	ON	OFF	ON
Tem. Comm.	2-1	OPEN	2-3

SPECIFICATIONS:

CONTACT RATING : 6 AMPS @ 120 V AC or 28 V DC.
 3AMPS @ 250 V AC or 0.4 Volt-AMPS max@ 20V AC or DC
 ELECTRICAL LIFE : 30,000 make-and-break cycles at full load.
 CONTACT RESISTANCE : 10 mΩ max. initial @ 2-4 V DC.
 100 mA, for both silver and gold plated contacts.
 INSULATION RESISTANCE : 1,000 MΩ min.
 DIELECTRIC STRENGTH : 1,000 V RMS @ sea level.
 OPERATING TEMPERATURE : -30 °C to 130 °C

MATERIALS:

CASE : Diallyl phthalate (DAP)(UL-94V-0).
 ACTUATOR : Nylon.
 HOUSING : Stainless steel.
 TERMINAL/CONTACT : Brass, with silver or gold plated.
 or gold over silver
 SWITCH SUPPORT : Brass, tin plated.

喜威達企業股份有限公司
 SWEETA PRODUCTS CORPORATION

23552 新北市中和區中正路799號1樓
 Tel : 02-2226-8001 Fax : 02-2226-8002
 http : //www.sweeta.com.tw E-mail : sweeta.tw@msa.hinet.net

TOLERANCE

XX, ± 0.5

X, ± 0.2

.X ± 0.2

.XX ± 0.2

ITEM NO	DATA
CHECKED BY	DRAWN BY